

CAMSO BHL 530

FORMERLY SOLIDEAL MR F3



BACKHOE
LOADERS



PERFORMANCE AND QUALITY YOU CAN RELY ON

Delivers reliable performance and quality for tough backhoe applications. Count on this all-purpose steer tire for excellent stability and improved operator comfort on a variety of surfaces.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO BHL 530



ENGINEERED F3 RIB TREAD DESIGN

- Provides smooth ride and effective steering



ROBUST CARCASS



- Reduces tread crowning for even wearing and excellent stability

DEEP TREAD DEPTH

- Enhances longevity

TIRE SIZE	PR	TT / TBLS	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE [bar] [PSI]	APPLI-CATION	MAXIMUM TIRE LOAD [kg] [lb]				
			Recommended	Alternative	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]					Static	8 km/h 5 mph	16 km/h 10 mph	40 km/h 25 mph	50 km/h 30 mph
11L-15SL	10	TBLS	8LBx15	10LBx15	768	280	13.5	118	B	3.00	-	2640	-	-	-	1320
					30.2	11.0	17			42.86		5850	-	-	-	2900
11L-16SL	12	TBLS	8LBx16	W8L, 10LB, W10Lx16	802	262	13.5	123	B	3.60	-	3110	-	-	-	155
					31.6	10.3	17			51.43		6850	-	-	-	3450
14.5/75-16.1SL	10	TBLS	W11Cx16.1	-	940	361	17	121	A8	2.80	-	4350	2480	2175	1450	-
					37.0	14.2	21			40.00		9600	5450	4800	3200	-

11L16 12PR BHL 530



The Camso BHL 530 front backhoe tire features a stronger carcass construction for **improved stability under load** with reduced tread crowning

■ VERTICAL DEFLECTION (mm) ■ HORIZONTAL DEFLECTION (mm)

AUTHORIZED DISTRIBUTOR:

camso.co

