



Pattern: LS-2A

## Description:

The design of the LS-2A gives the tyre excellent traction and good self-cleaning properties.

The design offers excellent puncture resistance as well as excellent cut and abrasion resistance making it suitable for forestry operations.

## TECHNICAL DATA:

SIZE	PLY	Pattern	Type	Load Index	Speed Symbol	Standard RIM	Overall Diameter ( mm )	Section Width ( mm )	Inflation Pressure ( kpa )	Loading Capacity		Tread Depth ( mm )
										(km/h)	(kg)	
26"												
18 . 4 - 26	14	LS-2A	TT	141	A6	16.00	1476	467	170	30	2575	51,00
23 . 1 - 26	14	LS-2A	TL/TT	157	A6	20.00	1632	587	210	30	4125	53,00
23 . 1 - 26	16	LS-2A	TT	160	A6	20.00	1632	587	240	30	4500	53,00
28 L - 26	14	LS-2A	TL	158	A6	25.00	1644	714	170	30	4250	55,00
28 L - 26	18	LS-2A	TL/TT	162	A6	25.00	1644	714	210	30	4750	55,00
28 L - 26	20	LS-2A	TL/TT	165	A6	25.00	1644	714	240	30	5150	55,00
30"												
16 . 9 - 30	10	LS-2A	TT	141	A6	15.00	1511	429	210	30	2575	48,00
18 . 4 - 30	16	LS-2A	TT	143	A6	16.00	1577	467	170	30	2725	51,00
32"												
24 . 5 - 32	16	LS-2A	TL/TT	164	A6	21.00	1831	622	210	30	5000	55,50
24 . 5 - 32	20	LS-2A	TT	167	A6	21.00	1831	622	240	30	5450	55,50
30 . 5L - 32	18	LS-2	TL/TT	169	A6	27.00	1847	775	210	30	5800	55,50
30 . 5L - 32	20	LS-2	TT	172	A6	27.00	1847	775	240	30	6300	55,50
34"												
18 . 4 - 34	10	LS-2A	TT	145	A6	16.00	1679	467	170	30	2900	51,00
18 . 4 - 34	12	LS-2A	TT	149	A6	16.00	1679	467	210	30	3250	51,00

### Legal Information:

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Guizhou Tyre Co., LTD. or any subsidiary or affiliated company does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication are the exclusive property of Guizhou Tyre Co., LTD. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish any contents in whole or in part on paper format and electronic format or otherwise without prior written consent by Guizhou Tyre Co., LTD.